

Recycled Content Tracking

The project referenced above will be pursuing the LEED credit for recycled content. To meet the requirements for this credit, the information requested below needs to be filled out for all materials with recycled content. Please provide the requested information along with supporting documentation.

Material Name	Manufacture	Material Cost w/ Markup (\$)	Post-Consumer Recycle Content (%)	Pre-Consumer Recycle Content (%)	Recycle Content Information Source
Bar	Nucor		83%	17%	Nucor
Beam	Nucor		47%	10%	Nucor
Plate	Nucor		79%	12%	Nucor
Sheets	Nucor		59%	12%	Nucor
Joist	CMC Joist		58%	42%	CMC Joist
Deck	Marlyn		80%	20%	Marlyn

Notes:

- " The recycled content percentages must be determined by weight.
- * Post-consumer material is defined as waste material generated by households or by commercial, industrial and institutional facilities in their role as end-users of the product, which can no longer be used for its intended purpose.
- * Pre-consumer material is defined as material diverted from the waste stream during the manufacturing process. Excluded is reutilization of materials, such as rework, regrind, or scrap generated in a process and capable of being reclaimed within the same process that generated it.
- * Do not include mechanical, electrical, and plumbing components or specialty items such as elevators and equipment

The undersigned subcontractor ensures that the information provided above is accurate and not misleading. The representative also ensures that the information has been substantiated and verified.

Regional Materials Tracking

The project referenced above will be pursuing the LEED credit for regional materials. To meet the requirements for this credit, the information requested below needs to be filled out for all materials from within 500 miles of the project site. Please provide the requested information along with supporting documentation.

Product Name	Manufacturer	Total Product Cost W/ Mark Up (\$)	Percent Compliant (0/0)	Compliant Product Value (\$)	Harvest Distance (mi)	Man. Distance (mi)	Harvest / Man. Location Info Source
Sheets	Nucor				672		Nucor
Bar	Nucor				624		Nucor
Beam	Nucor				672		Nucor
Plate	Nucor				586		Nucor
Joist	CMC				500		CMC
Deck	Marlyn				500		Marlyn

- Notes:
- * The product must be extracted, harvested, or recovered within 500 miles of the project site. * The product must be manufactured within 500 miles of the project site.
 - * If only a fraction of the product meets the distance requirements, then only that percentage (by weight) shall contribute to the regional value
 - * Do not include mechanical, electrical, and plumbing components or specialty items such as elevators and equipment

The undersigned subcontractor ensures that the information provided above is accurate and not misleading. The representative also ensures that the information has been substantiated and verified.

Low-Emitting Materials Tracking for Paints and Coatings

The project referenced above will be pursuing the LEED credit for low-emitting materials for paints and coatings. To meet the requirements for this credit, the information requested below needs to be filled out for all architectural paints, coatings, primers, anti-corrosive and anti-rust paints, clear wood finishes, floor coatings, stains, sealers, and shellacs. Please provide the requested information along with supporting documentation.

Anti-corrosive and Anti-rust Paints				
Architectural Paints, Coatings, and Primers				
Product Manufacturer	Product Name / Model	Product VOC Content (g/L)	Green Seal, GS-11, Allowable VOC Content	Source of VOC Data
Product Manufacturer	Product Name / Model	Product VOC Content (g/L)	Green Seal, GS-03, Allowable VOC Content	Source of VOC Data
Sumter Coatings	Red Primer	3.23		MSDS

Clear Wood Finishes, Floor Coatings, Stains, Sealers, and Shellacs				
Product Manufacturer	Product Name / Model	Product VOC Content (g/L)	S C A Q M D Allowable VOC Content (g/L)	Source of VOC Data

- Notes:
- * Applies to paints and coatings used on the interior of the building (defined as inside of the weatherproofing system and applied on-site)
 - * The Green Seal, GS-11, Allowable VOC Content should be obtained from the Green Seal Standard GS-11, Paints, First Edition, May 20, 1993
 - * The Green Seal, GS-03, Allowable VOC Content should be obtained from the Green Seal Standard GS-03, Anti-Corrosive Paints, Second Edition, January 7, 1997
 - * The SCAQMD Allowable VOC Content should be obtained from the South Coast Air Quality Management District (SCAQMD) Rule #1113, Architectural Coatings, rules in effect on January 1, 2004

The undersigned subcontractor ensures that the information provided above is accurate and not misleading. The representative also ensures that the information has been substantiated and verified.

Low-Emitting Materials Tracking for Adhesives and Sealants

The project referenced above will be pursuing the LEED credit for low-emitting materials for adhesives and sealants. To meet the requirements for this credit, the information requested below needs to be filled out for all adhesives, sealants, sealant primers, and aerosol adhesives. Please provide the requested information along with supporting documentation.

Aerosol Adhesives				
Adhesives, Sealants, and Sealant Primers				
Product Manufacturer	Product Name / Model	Product VOC Content (g/L)	SCAQMD Allowable VOC Content (g/L)	Source of VOC Data
Sumter Coatings	Red Primer	3.23	3.23	M S D S
Product Manufacturer	Product Name / Model	Product VOC Content (g/L)	Green Seal, GS-36, Allowable VOC Content	Source of VOC Data

Notes:

- * Applies to adhesives and sealants used on the interior of the building (defined as inside of the weatherproofing system and applied on-site)
- * The SCAQMD Allowable VOC Content should be obtained from the South Coast Air Quality Management District (SCAQMD) Rule #1168 with an effective date of July 1, 2005 and rule amendment date of January 7, 2005
- * The Green Seal, GS-36, Allowable VOC Content should be obtained from the Green Seal Standard for Commercial Adhesives GS-36 requirements in effect on October 19, 2000

The undersigned subcontractor ensures that the information provided above is accurate and not misleading. The representative also ensures that the information has been substantiated and verified.